

TM70 / IK2

Service, design and endless options



External removable
EEPROM SIM
module



IK 2

Characteristics

- Up to 2 joysticks or 4 paddles
- Toggle Switches, Pushbuttons, Selector Switches,
- Multiband Radio with Full-Duplex communication
- Highly customizable
- 128x64 Graphic LCD Display
- External removable EEPROM SIM module
- Easy and fast maintenance
- High resistance to impacts
- Innovative ergonomics
- Non-slip handles
- Frequency management against interferences

Specifications

Transmitter	IK2
Stop Function	Cat. 3 - PLd
Ingress Protection	IP65/NEMA4
Anti condensation system	Goretex Film
Frequency Band	Multiband (400 - 930 MHz)
Main Mechanisms (Max. #)	Joystick (2) / Paddle (4)
Auxiliary Mechanisms	Pushbutton, Toggle & Rotary switches
Removable EEPROM	External
Battery Model	BT11K
Battery Life	16h
Operating Temperature Range	-20C +70C (-4F +158F)
Weight (with Battery) Grams	950 (~ 2.1 lbs)
Harness	Belt / Shoulder Strap
Display	128x64 Graphic LCD
Cable Connection for Direct Link	YES (M12 Connector)
Range Limiter	YES
Associated Receivers	R70/R70PLUS/MR11/RCANCE/MP20/MP08