

Standard Crane Configuration Questionnaire

Prepared By: _____ Quote#: _____

OEM End User

Name: _____ Phone: _____ Fax: _____

Address: _____

Attn: _____ Email _____

End User: _____ Location: _____

Control Voltage: 120/230VAC 230VDC 9-35VDC

Freq. Operation: 450Hz 915Hz

Environment: Indoor Outdoor Intrinsic

Drawings: Customer Drawing Standard Stub Outs

Controller Type: Handheld Lever Joystick Detented Lever

Bridge: _____Speeds _____Stepless Compass Dir. _____ Outputs _____

Trolley: _____Speeds _____Stepless Compass Dir. _____ Outputs _____

Hoist: _____Speeds _____Stepless Compass Dir. _____ Outputs _____

Aux Hoist : _____Speeds _____Stepless Compass Dir. _____ Outputs _____

Aux Trolley: _____Speeds _____Stepless Compass Dir. _____ Outputs _____

Auxiliary Functions

- Brake Alarm Grab Rotate Lights Lights Latching
 Magnet Lift/Drop Magnet On/Off Trolley Hoist Select Display
 First Come First Served Range Limiting Mode Harness Harness Padded Belt

Receiver Type

- Standard (NEMA 4/IP65) NEMA 4X INTRINSIC

Transfer Switch

- Internal External Not Required Effective Full Isolation

Latching Relays Required

- 1 Relay 2 Relays 3 Relays

(Magnet On/Off, Lift Drop requires 2 latching relays in most applications)

Installed on Enclosure: Horn Light Connector on Pigtail

Stepless Output Voltage: 0-10VDC 0-20VDC 0-20VAC 0-80VAC

Special Notes: _____

