

MU-9X15

900MHz @ 100mW

WARRIOR RECEIVERS

Channel-Hopping DSSS ■ FCC & Industry Canada License-Free ■ External Antenna (RP-TNC)

POWER

OPERATING VOLTAGE

HIGH VOLTAGE: 115-230VAC @ 50-60HZ

LOW VOLTAGE: 9-36VDC OR 10-28VAC @ 50-60HZ

OPERATING POWER

2.4W MAXIMUM

CONTROLS

CONTROL RELAYS

FUNCTION: NINE FORM A, 8A @ 250VAC

SYSTEM: THREE BANKS OF THREE FORM A,
EACH BANK FUSED AT 5A @ 250VAC

MAIN LINE CONTACTOR

SAFETY CIRCUIT: TWO (SERIES) TYPE FORM A, 8A @ 250VAC
FUSED @ 5A @ 250VAC

ISOLATED RELAYS

INDEPENDENT FOUR FORM A, 8A @ 250VAC

INPUT FUSE

LINE ONE 2A @ 250VAC

LEDs

ONE STROBE LED (WHITE)

USED DURING ASSOCIATION

ENVIRONMENT

OPERATING TEMPERATURE

-25°C TO 70°C (-13°F TO 158°F)

STORAGE TEMPERATURE

-40°C TO 80°C (-40°F TO 176°F)

HUMIDITY

0 TO 95% NON-CONDENSING

