CERVIS

CB-xW CONSOLE BOX

WARRIOR TRANSMITTER

POWER

OPERATING VOLTAGE

+2.0 TO +3.2 VDC: TWO "C" 1.5V CELL BATTERIES +2.7 TO +4.2 VDC: RECHARGEABLE NIMH BATTERY PACK

NIMH BATTERY PACK

VOLTAGE: 3.6 VDC NOMINAL CAPACITY: 2000 MAH NOMINAL CERVIS P/N: 2208001

CONTROLS

JOYSTICKS UP TO FOUR SINGLE-AXIS, MODEL-DEPENDENT

LEVERS UP TO SIX SINGLE-AXIS (Y+, Y-)

TOGGLES

TWO- OR THREE-POSITION (MAINTAINED OR MOMENTARY) MODEL-DEPENDENT

PUSHBUTTONS ONE (OPTIONS AVAILABLE)

STOP TWO-POSITION

LEDs (all red)

FOUR (RED)

 FLASHES WHEN A MESSAGE IS TRANSMITTED OR RECEIVED
SLOW BLINKS - LESS THAN 1 HOUR OF RUNTIME REMAINING
LIT WHEN A IS SELECTED
LIT WHEN B IS SELECTED

ENVIRONMENT

OPERATING TEMPERATURE -4°F TO 131°F (-20°C TO 55°C)

STORAGE TEMPERATURE -40°F TO 185°F (-20°C TO 85°C)

HUMIDITY 0 TO 95% NON-CONDENSING

900MHz @ 100mW

Channel-Hopping DSSS 🔳 FCC & Industry Canada License-Free 🔳 Internal Antenna

