

# Cervis Standard Crane Configuration Questionnaire

Prepared By: \_\_\_\_\_ Quote#: \_\_\_\_\_

OEM  Distributor/Reseller  End User

Name: \_\_\_\_\_ Phone: \_\_\_\_\_ Fax: \_\_\_\_\_

Address: \_\_\_\_\_ Attention: \_\_\_\_\_ Email: \_\_\_\_\_

End User: \_\_\_\_\_ Location: \_\_\_\_\_

Control Voltage:  120/230VAC  230VDC  9-35VDC  Other

Environment:  Indoor  Outdoor

Drawings Available:  Yes  No

Controller Type:  Handheld Pushbutton  Console Box Joystick  Console Box Detented Lever  Console Box Stepless

Bridge: Speeds \_\_\_\_\_ Stepless \_\_\_\_\_ Compass Direction \_\_\_\_\_ Outputs Required \_\_\_\_\_

Trolley: Speeds \_\_\_\_\_ Stepless \_\_\_\_\_ Compass Direction \_\_\_\_\_ Outputs Required \_\_\_\_\_

Hoist: Speeds \_\_\_\_\_ Stepless \_\_\_\_\_ Compass Direction \_\_\_\_\_ Outputs Required \_\_\_\_\_

Auxiliary Hoist: Speeds \_\_\_\_\_ Stepless \_\_\_\_\_ Compass Direction \_\_\_\_\_ Outputs Required \_\_\_\_\_

Auxiliary Trolley: Speeds \_\_\_\_\_ Stepless \_\_\_\_\_ Compass Direction \_\_\_\_\_ Outputs Required \_\_\_\_\_

### Auxiliary Functions:

Brake  Alarm  Grab  Rotate  Lights  Lights Latching  
 Magnet Lift/Drop  Magnet On/Off  Trolley Hoist Select  Display  First Come First Served  
 Range Limiting Mode  Harness  Harness Padded  Belt  PTO Enable

### Receiver Type:

Standard (NEMA 4/IP65)  Custom / Specify \_\_\_\_\_

### Transfer Switch:

Internal  External  Not Required  Effective  Full Isolation

### Latching Relays Required:

1 Relay  2 Relays  3 Relays

*(Magnet On/Off, Lift Drop, Magnet Power (rectifier for AC?), requires 2 latching relays in most applications)*

Stepless Output Voltage:  0-10VDC  0-20VDC  0-20VAC  0-80VAC

### Additional Notes: